



PANEL

PREMIER CONCEPTS | DATA SHEET

The Premier Concepts Wall & Ceiling Panels feature premium grade veneers or high pressure laminates adhered to a wood substrate. Panels are manufactured in our North Carolina facility and can be shipped to the jobsite finished and ready for install or in full panels with supplied loose edgbanding. Panels are manufactured in sizes up to 4' by 12'.



ACCLIMITIZATION

Required before installation
Relative humidity: 25 - 55% | **Temperatures:** 50° - 86° F



FIRE PERFORMANCE

Can be treated to meet Class A as per ASTM E-84. Veneers are applied to a FR (Fire Related) core (typically MDF or Particleboard).



SUSPENSION

Should be suspended using standard 15/6 heavy duty grid. Regular or Lay in ceilings may be suspended using standard 9/16" heavy duty grid. Mains for 15/16" heavy duty grid shall be a max of 2' on center.



SYSTEM WEIGHT

Typically weigh 2-4 pounds per square foot



ACOUSTICS

Wall & Ceiling Panels can be installed with perforations allowing sound to pass through. Wall & ceiling panels are accoustically reflective.



MATERIALS

Wide range of solid wood, veneers & laminates



FINISHES

Standard clear & matte - custom available



SUSTAINABILITY

Custom fabricated for your project. Contact sales to find out if your project qualifies for LEED credit opportunities.



SEISMIC

Panel meets code compliance via direct screw attachment to heavy duty grid. Local code should be consulted to determine additional seismic requirements.



PREMIER CONCEPTS

919-363-3986

sales@premierconceptusa.com

151 Premier Drive
 Holly Springs, NC 27540

PANEL



SPECIFICATIONS

SIZE	
Panel dimensions	Manufactured in sizes up to 4' x 12'

WALL & CEILING PANEL (TOP VIEW)



WALL & CEILING PANEL (SIDE VIEW)

